

Agder 12-36

Elnummer: 3254627

EAN: 7070913015159



General data

Installation type	Surface
Light source	LED
Color	White

Electrical properties

Power	36W
Operating voltage	AC 220-240V 50/60Hz
Driver	non-dimmable
Driver included	Yes
Insulation class	Class I
Dimmable	No

Protection and safety

Ingress protection (IP) rating	IP65
IK classification	-
Ambient temperature	-20 to 40°C
Isosafe	-

Installation and mechanical properties

Through-wiring	3x2.5mm ²
Cutout	-
Construction height	71 mm
Gyroscopic	-
DxH (Diameter x Height)	1200*83*71 mm
Material	PC

Light performance and quality

Lumen	4140 Lm (3000K)
	4680 Lm (4000K)
	4320 Lm (5000K)
	115 Lm/W (3000K)
Lumens per watt	130 Lm/W (4000K)
	120 Lm/W (5000K)
Color temperature	3000K-4000K-5000K
Color rendering index (CRI)	≥80
SDCM / MacAdam step	≤3
Light distribution	120°
Optics	Reflector
UGR (Unified Glare Rating)	39

Lifetime at 25°C

Lifetime 50,000 hours	L90B10
Lifetime 100,000 hours	L80B20

Energy and environment

Energy class	D
--------------	---

