

# Agder 15-45 DALI

Elnummer: 3254658

EAN: 7070913016804



## General data

|                   |         |
|-------------------|---------|
| Installation type | Surface |
| Light source      | LED     |
| Color             | White   |

## Electrical properties

|                   |                     |
|-------------------|---------------------|
| Power             | 45W                 |
| Operating voltage | AC 220-240V 50/60Hz |
| Driver            | non-dimmable        |
| Driver included   | Yes                 |
| Insulation class  | Class I             |
| Dimmable          | No                  |

## Protection and safety

|                                |             |
|--------------------------------|-------------|
| Ingress protection (IP) rating | IP65        |
| IK classification              | -           |
| Ambient temperature            | -20 to 40°C |
| Isosafe                        | -           |

## Installation and mechanical properties

|                         |                       |
|-------------------------|-----------------------|
| Through-wiring          | 3x 2.5mm <sup>2</sup> |
| Cutout                  | -                     |
| Construction height     | 71 mm                 |
| Gyroscopic              | -                     |
| DxH (Diameter x Height) | 1500*83*71 mm         |
| Material                | PC                    |

## Light performance and quality

|                             |                                                          |
|-----------------------------|----------------------------------------------------------|
| Lumen                       | 5175 Lm (3000K)<br>5850 Lm (4000K)<br>5400 Lm (5000K)    |
| Lumens per watt             | 115 Lm/W (3000K)<br>130 Lm/W (4000K)<br>120 Lm/W (5000K) |
| Color temperature           | 3000K-4000K-5000K                                        |
| Color rendering index (CRI) | ≥80                                                      |
| SDCM / MacAdam step         | ≤3                                                       |
| Light distribution          | 120°                                                     |
| Optics                      | Reflector                                                |
| UGR (Unified Glare Rating)  | 39                                                       |

## Lifetime at 25°C

|                        |        |
|------------------------|--------|
| Lifetime 50,000 hours  | L90B10 |
| Lifetime 100,000 hours | L80B20 |

## Energy and environment

|              |   |
|--------------|---|
| Energy class | D |
|--------------|---|

