



HAV 15-40

Elnummer: **3254679**
 EAN: 7070913021006



General data

Installation type Suspension/ Surface
 Light source LED
 Color White

Electrical properties

Power 26/33/40/47W
 Operating voltage AC 220-240V 50/60Hz
 Driver Power adjustable driver
 Driver included yes
 Insulation class Class I
 Dimmable No

Protection and safety

Ingress protection (IP) rating IP44
 IK classification IK07
 Ambient temperature -20 to 40°C
 Isosafe -

Installation and mechanical properties

Through-wiring 5*2.5mm²
 Cutout -
 Construction height -
 Gyroscopic -
 DxH (Diameter x Height) 1500*155*52mm
 Material Metal coated+PMMA

Light performance and quality

Lumen 3640/4620/5600/6580 lumen
 Lumens per watt 140 lm/w ved 4000K
 Color temperature 3000K/4000K
 Color rendering index (CRI) 80
 SDCM / MacAdam step 3
 Light distribution 110°
 Optics Diffusor
 UGR (Unified Glare Rating) 22

Lifetime at 25°C

Lifetime 50,000 hours L90/B10
 Lifetime 100,000 hours L80/B10

Energy and environment

Energy class D

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM

