



HAV 15-40 sensor

Elnummer: **3254680**

EAN: 7070913021044


IP44


General data

Installation type	Suspension/ Surface
Light source	LED
Color	White

Electrical properties

Power	26/33/40/47w
Operating voltage	AC 220-240V 50/60Hz
Driver	Power adjustable driver
Driver included	yes
Insulation class	Class I
Dimmable	No

Protection and safety

Ingress protection (IP) rating	IP44
IK classification	IK 07
Ambient temperature	-20 to 40°C
Isosafe	-

Installation and mechanical properties

Through-wiring	5*2.5mm ²
Cutout	-
Construction height	-
Gyroscopic	-
DxH (Diameter x Height)	1500*155*52mm
Material	Metal coated+PMMA

Light performance and quality

Lumen	3640/4620/5600/6580 lumen
Lumens per watt	140 lm/w ved 4000K
Color temperature	3000K/4000K
Color rendering index (CRI)	80
SDCM / MacAdam step	3
Light distribution	110°
Optics	Diffusor
UGR (Unified Glare Rating)	22

Lifetime at 25°C

Lifetime 50,000 hours	L90/B10
Lifetime 100,000 hours	L80/B10

Energy and environment

Energy class	D
--------------	---

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM

