

Fonda 12W IP20 3000K

Elnummer: 3253701

EAN: 7070913002180



General data

| | |
|-------------------|---------|
| Installation type | Surface |
| Light source | LED |
| Color | White |

Electrical properties

| | |
|-------------------|---------------------|
| Power | 12 W |
| Operating voltage | AC 220-240V 50/60Hz |
| Driver | non-dimmable |
| Driver included | Yes |
| Insulation class | Class I |
| Dimmable | No |

Protection and safety

| | |
|--------------------------------|-------------|
| Ingress protection (IP) rating | IP20 |
| IK classification | - |
| Ambient temperature | -20 to 40°C |
| Isosafe | - |

Installation and mechanical properties

| | |
|-------------------------|-------------|
| Through-wiring | - |
| Cutout | - |
| Construction height | 100 mm |
| Gyroscopic | - |
| DxH (Diameter x Height) | Φ330*100 mm |
| Material | Iron, PMMA |

Light performance and quality

| | |
|-----------------------------|-----------|
| Lumen | 780 Lm |
| Lumens per watt | 65 Lm/W |
| Color temperature | 3000 K |
| Color rendering index (CRI) | ≥80 |
| SDCM / MacAdam step | ≤6 |
| Light distribution | 120° |
| Optics | Reflector |
| UGR (Unified Glare Rating) | 24 |

Lifetime at 25°C

| | |
|------------------------|--------|
| Lifetime 50,000 hours | L90B10 |
| Lifetime 100,000 hours | L80B20 |

Energy and environment

| | |
|--------------|---------------|
| Energy class | E(LED MODULE) |
|--------------|---------------|

