



HAV 12-40

Elnummer: 3254664

EAN: 7070913017283



General data

Installation type	Suspension/ Surface
Light source	LED
Color	White

Electrical properties

Power	23/29/35/40w
Operating voltage	AC 220-240V 50/60Hz
Driver	Power adjustable driver
Driver included	yes
Insulation class	Class I
Dimmable	No

Protection and safety

Ingress protection (IP) rating	IP44
IK classification	IK07
Ambient temperature	-20 to 40°C
Isosafe	-

Installation and mechanical properties

Through-wiring	5*2.5mm ²
Cutout	-
Construction height	-
Gyroscopic	-
DxH (Diameter x Height)	1200mm*155mm*52mm
Material	Metal Coated+PMMA

Light performance and quality

Lumen	3220/4060/4900/5600lm
Lumens per watt	140 lm/w ved 4000K
Color temperature	3000K/4000K
Color rendering index (CRI)	80
SDCM / MacAdam step	3
Light distribution	110°
Optics	Diffusor
UGR (Unified Glare Rating)	22

Lifetime at 25°C

Lifetime 50,000 hours	L90/B10
Lifetime 100,000 hours	L80/B10

Energy and environment

Energy class	C
--------------	---

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM

