

SPECIFICATION

Description	220-240V LED Driver, Constant Current Driver
Electrical Characteristics	Ta = 25°C, 220-240Vrms input, standard reference load; unless otherwise specified
Class II, IP20, thermally protected	110°C, independent driver

Product Name		3253514
Input Parameters		
Rated Input Voltage	Uin	220-240VAC
Input Current (Full load)	Iin	0.23A
Input Frequency	fin	50/60Hz
Maximum Input Power	Pin	47W
Power Factor (Full load)	λ	≥ 0.95
THD(Full load)		$\leq 15\%$
Efficiency (Full load)	η	$\geq 88\%$
No-load power		$\leq 0.5W$
Inrush current(Cold start)	Apk	25(th=300us)
Turn on time		$\leq 500ms$

Output Parameters		
Output Voltage	Vout	19-38V
Output Current (Full load)	Iout	1050mA $\pm 5\%$
Output Power (Full load)	Pout	40W
Operating Frequency(Full load)	Fout	60KHz
Ripple & Noise		$\leq 50mA$
Load Regulation		$\leq 5\%$
Line Regulation		$\leq 5\%$


Ambient		
Storage Temperature	ts	-20 ...+ 70°C
Operating Ambient Temperature	ta	-20 ...+ 40°C
Case Temperature at tc Point	tc	70°C
Relative humidity		5 ...85%

Protection		
No Load		Auto-recovery if fault is removed
Over Load		Auto-recovery if fault is removed
Short Circuit		Auto-recovery if fault is removed

System Parameters		
Withstand voltage		3.75KVAC, Ileakage<5.0mA, 60s
Expected Life		100,000 Hours

Compliances and approvals		
Safety		EN 61347-2-13
RFI		EN 55015
Harmonics		EN 61000-3-2 Class C
Immunity		EN 61547

Note		
1. All parameters NOT specially mentioned are measured at 240VAC input, rated load and 25 of ambient temperature.		
2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uF & 47uF parallel capacitor.		
3. Expected Life:tc=80°C,0.2%/1000h failure rate		

Physical Parameter		
 Dimensions(LxWxH): 127x43x28mm Housing Material: PC Plastic Captured Terminal Screw for 0.75~2.5mm²		